

- N2-210X
- N2-220X

KEY FEATURES



- NDI HX3 Certified
- Zoom: Optical 10X, 20X
- Video Output: NDI HX3, HDMI, SDI, USB C
- Horizontal Angel of View: 69°
- Video Resolution up to Full HD
- IP resolution up to 1080P60.
- RTSP, RTMP, SRT IP streaming
- AI Exposure, AI Focus
- Power: 12VDC, PoE



OVERVIEW

Bolin’s N-Series PTZ cameras support NDI® HX3 and are fully compatible with NDI-enabled hardware and software. They are built on the Blue Line platform, which provides gold-standard features at an affordable price.

Our PTZ camera manufacturing principles never compromise image quality, industrial video standards, or PTZ control operation. So, these budget-friendly cameras are made with Bolin care and quality.

The N2 NDI HX3 PTZ camera has a compact design and form factor. The two models N2-210X, N2-220X feature a 10x or 20x wide-angle view, with a high-quality Full HD image output over NDI®, HDMI, 3G-SDI (N2-220X only), USB, and IP video streams. They are perfect for studio, live production, house of worship, huddle rooms, video conference rooms, and ProAV use.



Interoperability | Low Latency | High Quality

## FUNCTIONALITY

- N2-210X and N2-220X is equipped with Sony sensor to provide brilliant, high-quality images in 1080p60 resolutions with 10X or 20x optical zoom range.
- Compact design and USB 2.0 (C Type) video used for Huddle Space cloud based video conferencing application.
- N2-210X/N2-220X cameras deliver NDI HX3 streaming video to network with local HDMI video and USB streaming to PC software for conventional video production and cloud based video conferencing applications. N2-220X also provides 3G-SDI, lossless baseband video for live production and light broadcast use.
- Image parameter adjustments includes exposure, focus, iris, shutter speed, white balance, gamma, wide dynamic range, image stabilizer, flip/mirror and more with configurable video settings.
- Another Gold Standard feature of the Blue Line is the Color Matrix. With it, you can easily make subtle and specific corrections to the colors in your camera's image.
- Built with Bolin's latest AI-powered facial analytics engine, which enables smart focus and smart exposure to provide faster, more precise focusing and improved auto exposure on faces in complex lighting environments.
- HDMI/SDI/USB and IP video has high-quality audio streaming embedded with support for Mic-in and Line-in audio input.
- Extremely quiet and smooth operation for Pan/Tilt movements combined with enhanced adaptive, variable, and super slow adaptive speed control provides accurate and effective operation experiences. Picture Profile Preset: Image parameter settings restored with presets and quick access operation.
- Support 1GB Ethernet network, independent PoE+ (IEEE 802.3at) power and 12VDC; Standard mounting and ceiling mounting with E-Flip function.
- Firmware updates, upgrade via IP interface to keep camera features and performance up to date.



N2-210X



N2-220X

# Product Specification

Model No.	N2-210X	N2-220X
Camera	10X Full HD	20X Full HD
Image Sensor	Sony Progressive scan CMOS image sensor 1/2.8 type	
Number of effective pixels	1920X1080, 2.13 MP	1920X1080, 2.13 MP
Zoom	Optical Zoom 10X, Digital Zoom 16X	Optical Zoom 20X, Digital Zoom 16X
Focal Length	f= 4.34 mm (Wide) to 35.17 mm (Tele)	f= 5.2 mm (Wide) to 104 mm (Tele)
Aperture	F1.85 (Wide) to F2.63 (Tele)	F1.6 (Wide) to F3.0 (Tele)
Horizontal Angle of View	68.8 °(W)~8.8° (T)	55.8° (W)~3.2° (T)
Vertical Angle of View	39.5° (W)~5.1° (T)	-
Min. object distance	10mm (Wide)	
Min. Illumination	0.5lux (color) , 0.1lux (black)	
Shutter Speed	1/1 sec to 1/10000 sec (22 steps)	
Focus	Auto, Manual, One Push	
White Balance	Auto, Indoor, Outdoor, OPW, ATW, Manual	
Exposure	Auto, Manual, Shutter /Iris /Brightness priority	
Image Adjustment	Brightness, Color(Saturation), Contrast, Sharpness, HUE	
Back Light Compensation	On/Off	
E-Flip	On/Off	
WDR	On/Off	
Image Stabilizer	-	
Defog	-	
Mirror	Horizontal	
Day/Night	On/Off	
Contrast	Yes	
Color Gain	Yes	
Color Hue	Yes	
Color Matrix	Yes	
Black Level	-	
Gamma	Yes, 0-4	
High Sensitivity	Yes	
Scene	Default, Clear, Bright, Soft	
Focus Zone	Face Priority, All Area, Upper Area, Central Area, Lower Area	
AI Face Detection Focus	Yes	
AI Face Auto Exposure	Yes	
Noise Reduction	2D/3D, 1-255	
S/N Ratio	≥50db	
OSD	Editable	
<b>HDMI Signal System</b>		
Video Format - HDMI	1920x1080p:60/59.94/50/30/29.97/25; 1280x720p:60/59.94/50/30/25	
Color Format	10bit(HDMI), YCbCr	
Color Space	YUV, RGB	
OSD Menu Display	YES	
<b>SDI Signal System</b>		
SDI Video Format	-	1080p:60/59.94/50/30/29.97/25; 720p:60/59.94/50/30/25
Color Precision	-	10bit(SDI), YCbCr, 4:2:2
Color Space	-	YUV
Standard	-	3G-SDI, SMPTE424/SMPTE292, TE 425-A(3Gb/s) standard / 75 Ω (BNC x 1), With SMPTE352 SDI Metadata Supported
True Dual Output	-	SDI and HDMI has same video format when HDMI outputs FHD and lower.
OSD Menu Display	-	YES
<b>USB Signal System</b>		
USB Port	USB2.0, Type C	
Encoder	H.264/MJPEG/YUV2	
USB Video Format	1920x1080p60/50/30/25fps , 1280X720p60/50/30/25fps	
Compatible Integration	UVC, UAC	
Video Conference Compatibility	Most video conference platform in the market	
<b>Network-IP Streaming</b>		
Video Codec	NDI HX3 (AVC/HEVC-H.264/265 by SoC)	
Network Interface	RJ45 port-Standard 1Gbps Ethernet	
IP Video - 1st Stream	1920x1080, 1280x720; Frame Rate: P60/50/30/25	
IP Video - 2nd Stream	704x576, 640x480, 640x360, 576x480, 352x228, 320x240, 320x180; Frame Rate P60/50/30/25	
True Dual Output	Video resolution and framerate: IP and HDMI can be output with different format (SDI and HDMI will be the same, SDI is the same or lower than HDMI, USB is the same as IP)	
IP Protocols	TCP/IP, ICMP, ARP, RTP, SIP, UDP, HTTP, HTTPS, DNS, DHCP, FTP, NTP, NDI	
Application Protocols	RTP, RTSP, RTMP, RTMPS, SRT, NDI	
Multi-stream	2 Streams (Up to 20 viewers at the same time)	
Audio Compression	AAC-LC, G.711, G.726 Broadband Audio Encoding	

# Product Specification

Model No.	N2-210X	N2-220X
Camera	10X Full HD	20X Full HD
<b>Network-IP Streaming</b>		
Compatible Integration	ONVIF2.4 (Profile S, Profile G, Profile T), VISCA Over IP	
OSD	Customized OSD	
Browser Support	Cross Browser Compatibility - HTML5 support for Microsoft Edge, Google Chrome, Firefox, and Safari	
Latency - Codec	NDI HX3 Certified, <100ms at 1080p60	
Bandwidth	50Mbps at 1080p60	
	Results may vary depending on network configuration and management settings.	
<b>Interface</b>		
HDMI Video Output	HDMI 1.4X1 Type A	
IP Video Stream	Up to 1080p60	
SDI Video Output	-	3G-SDI, SMPTE424/SMPTE292, TE 425-A(3Gb/s) standard / 75 Ω (BNC x 1), With SMPTE352 SDI Metadata Supported
HDBaseT Module	-	
Fiber Optic SDI Module	-	
Camera Control Interface	RJ45X1-RS422, RJ45X1-IP Control, IR Remote Control	
Control Protocol	VISCA, VISCA Over IP, Pelco P/D	
LAN Port	RJ45X1 (1000BASE-T Ethernet port)	
USB Port	USB2.0, Type C	
USB Protocol	UVC, UAC	
Synchronization	Internal synchronization	
Tally Light	Tally lamp in front, Red and Green Color	
Dip Switch	Camera bottom panel: 8 PIN x 2	
Firmware Upgrade	Upgrade via IP for camera system MCU and Encoder	
IR ID	ID selector for IR controller, total 3	
Power Connector Type	DC12V (IEC60130-10 (JEITA standard RC-5320A) TYPE4 ) INPUT: RJ45, PoE+ (IEEE802.3at)	
Audio Input	MIC/LINE input, 3.5mm audio jack ACC (Bit Rate(bps)48K*/96K; Sampling Rate(bps)16/24*/32	USB port to 3.5mm audio jack
Audio Output	-	USB port to 3.5mm audio jack-
Audio Output	Embedded with HDMI/SDI/IP streaming, 24bit Stereo, sample rate: 44k1 to 192k, PCM24	
Audio S/N Ratio	≥85dB	
Audio THD+N	≤0.05%	
Audio Noise (RMS)	≤-90dB	
<b>Mechanical</b>		
Pan Movement	Horizontal:±170 degrees continuous pan (Zoom Adaptive Speed Range: 0.05°~100°/S )	
Tilt Movement	Vertical:+90 degrees to -30 degrees (Zoom Adaptive Speed Range: 0.05°~50°/S)	
Speed Proportional	Pan/Tilt Speed proportional to zoom range	
Preset Position	255 positions, Speed 150°/s, Accuracy: 0.05° 6 presets on remote controller	
Preset Speed	0~5 Level Adjustable	
Preset Memory	YES, ( Picture Profile Preset-Preset Memory for image parameters, like: Backlight Compensation, White Balance, R-Gain/B-Gain, Auto Exposure, Bright, Iris, Shutter, Gain, Aperture, Effect, Noise Reduction, Mirror, Gamma, Ex-COMP, Color Hue, Contrast etc.)	
Motionless Preset	On/Off	
PTZ Trace Memory	Yes, 4 (Supported via IP interface)	
Cruise	Yes,4	
Adaptive PT	Zoom range adaptive Pan/Tilt speed	
Pan/Tilt Direction	Normal, Invert	
Quietness	NC35 or less	
Home Position	Support	
Environmental	Indoor	
<b>General</b>		
Body	Partial Magnesium Alloy	
Mount	Ceiling mount, Wall mount, Tripod	
Size of Tripod Screw Hole	1/4"-20UNC with safety joint	
Operating Temperature	-10 to +50 (°C), 32 to 130 (°F)	
Operating Humidity	≤80% Suitable for Use	
Power Input	DC±12V, PoE+(Compatible with IEEE802.3at)	
Power Consumption	Min:10W(Static state with no movement); Max:13W(Fully loaded operation)	
Dimension	143x143x161mm (LxWxH)	
Weight	1.5kg (Net weight)	
Body Color	Available in Black, White	
<b>Accessory</b>		
Power Supply	12VDC 4A X1, Universal various power core.	
Remote Controller	Full Function IR Controller X1	
Serial Control Adaptor	RS232/RS422 adapter cable x1 For serial RS232/422 control	

## ORDER INFORMATION

- N2-210X (10X, Black)
- N2-210W (10X, White)
- N2-220X (20X, Black)
- N2-220W (20X, White)